

INSTALLATION INSTRUCTIONS

UNIVERSAL HELMET LOCK, 7/8" TO 1-1/4" TUBING

4220 CHROME OR 4618 GLOSS BLACK

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

▲ WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

A CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- Universal Helmet Lock Assembly
- 1 Kevs
- Tamper-Proof Screws

YOU WILL ALSO NEED:

Flathead screw driver

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY NOTICE AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

STEP 2 Test fit the helmet lock on the motorcycle to ensure that the helmet will not damage or interfere with any other

components on your motorcycle.

DO NOT INSTALL THE TAMPER-PROOF SCREWS AT THIS TIME.

IT IS VERY IMPORTANT TO PERFORM THE "TEST-FIT" DUE TO NOTICE THE EXTREME DIFFICULTY IN REMOVING THE TAMPER-PROOF

SCREWS AFTER THEY ARE TIGHTENED.

ENSURE CLEARANCE OF PAINTED SURFACES THAT COULD BE DAMAGED BY A HELMET OR HOT SURFACES THAT COULD CAUSE DAMAGE TO YOUR HELMET.

STEP 3 Insert the tamper-proof screws through the front side of the helmet lock as shown in PIC.2.

STEP 4 Tighten the screws evenly and ensure that the helmet lock is properly clamped onto the tube.





KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM 454 COUNTY ROAD VV SOMERSET, WI 54025











INSTALLATION INSTRUCTIONS

UNIVERSAL HELMET LOCK, 7/8" TO 1-1/4" TUBING

-CONTINUED-

LOCK OPERATION

STEP 1 Insert key into lock; turn clockwise to open latch.

STEP 2 Loop helmet strap over the lock latch; shut the latch.

STEP 3 Turn the key counter-clockwise and remove the key to lock

the latch.

STEP 4 Repeat Step 1 to remove helmet.

AVOID LOSS OF CONTROL, DAMAGE AND SERIOUS INJURY OR **▲** WARNING DEATH. DO NOT OPERATE THE MOTORCYCLE WITH THE HELMET

LOCKED INTO THE UNIVERSAL HELMET LOCK.

ENSURE THAT THIS PRODUCT DOES NOT INTERFERE WITH THE **▲** WARNING PROPER AND SAFE OPERATION OF THE MOTORCYCLE. FAILURE TO INSTALL THIS PRODUCT COULD LEAD TO LOSS OF CONTROL

RESULTING IN SERIOUS INJURY OR DEATH.

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT NOTICE

ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL

FASTENERS.



LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- 1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- 2. The product must be properly installed, maintained & operated under normal conditions.
- 3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
- 4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- 5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
- 6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM 454 COUNTY ROAD VV SOMERSET, WI 54025







